



### Key Features

- H.264/MPEG-4 video stream input
- Up to 5 Megapixels (2560×1920) resolution
- VGA output at 1024×768 resolution
- 4-ch synchronous playback
- HDD group management
- 2 SATA interfaces

### Specifications

| Video / Audio Input    |   |
|------------------------|---|
| IP Video input         | 8-ch 4CIF real time or 4-ch 720P / UXGA / 1080P real time or 2-ch 2560×1920 not real time |
| Audio input            | 1-ch, RCA(2.0 Vp-p, 1 kΩ), for voice talk input   |
| Video / Audio Output   |   |
| VGA output             | 1-ch, resolution: 1024×768 /60 Hz   |
| Playback resolution    | 2560×1920 / UXGA / 1080P / 720P / 4CIF / VGA / DCIF / 2CIF / CIF / QCIF                   |
| Video output           | 1-ch, BNC (PAL: 704×576, NTSC: 704×480)   |
| Frame rate             | 25fps (P) / 30fps (N)   |
| Video bit rate         | 32Kbps~2048Kbps, or user defined (max. 16384 Kbps)  |
| Audio output           | 1-ch, RCA(2.0 Vp-p, 1 kΩ), for voice talk output  |
| Audio bit rate         | 16kbps  |
| Synchronous playback   | 4-ch  |
| Hard disk              |   |
| SATA                   | 2 SATA interfaces   |
| Capacity               | Up to 2TB capacity for each disk  |
| External interface     |   |
| Network interface      | 1, RJ45 10M / 100M self-adaptive ethernet interface                                       |
| Serial interface       | 1 RS-485 interface  |
| USB interface          | 2, USB2.0   |
| Alarm in               | 4   |
| Alarm out              | 1   |
| General                |   |
| Power supply           | 12 VDC  |
| Consumption            | ≤ 12W (without hard disk or DVD-R/W)  |
| Working temperature    | -10 °C ~ +55 °C   |
| Working humidity       | 10%~90%   |
| Dimensions (W x D x H) | 445 × 290 × 44 mm   |
| Weight                 | ≤ 8kg (without HDD or DVD-R/W)  |

#### Rear Panel



1. USB interface
2. Video out
3. Audio in
4. Audio out
5. LAN
6. VGA interface
7. RS-485 interface, alarm in, alarm out
8. 12 VDC power supply
9. GND
10. Power switch