

PS-1606K

Single door Access Controller

Single door Access Controller

Single Access Controller that is specially design for the Office building, Factory employee dormitory, and building commonality passage , offer a access controller solution with simpleness directly and competitive price for consumer

Features

- New ultrathin and simple design.
- Standalone, No Control Panels ,single door control.
- Easy and simple to use.
- Design of dustproof and high security.
- Has a flat back so it's easy to install on any flat surface
- Operating Mode: Card only, Keypad only, Card with Keypad or Facility Code only.
- Card capacity is 1600 users.
- Programmable door release time: 1~250 seconds
- Access code can be added or deleted by keypad management.
- Built-in electric buzzer for audible card entry and programming.
- Data is protected even after power failure.
- Machined housing in high durable.
- With hidden code function under keypad only open door mode.
- ISO Mifare one /EM-ID thin card or keyfob optional
- Can be connected with an external reader (3 S)



Product Feature

| Parameter | Model | PS-1606K |
|-----------------|-------|---|
| Display | | Red-power plot, Black-access granted, Yellow-Beep |
| Keypad | | 3 x 4 Flat membrane |
| Power | | DC12V 3Amp |
| Color | | Black or Ivory-white |
| Frequency | | 13.56Mhz or 125khz |
| Temperature | | (-10° C~70° C) |
| Humidity | | 10%~80%RH |
| Dimensions | | 86(L) x 86(W) x 18(H) MM |
| Box Dimensions | | 150(L) x 140(W) x 40(H) MM |
| Weight | | 200g |
| Reading range | | Within 10cm |
| Output format | | Wiegand26 bits |
| External reader | | Not support |