




#### Key Features

- HDCVI BNC interface, Support Over 500m via 75Ω coaxial cable
- long distance real-time transmission
- High definition video /Audio /RS485 transmission
- Support Day/Night (ICR)
- 3D-DNR and superior performance of low illumination
- 40M (2xIRIII)Support Smart IR
- Protection : IP66

#### Dimension



#### SPECIFICATION

Model	PS-172CVI
Parameter	1 / 2.9" 1.0M(1280*720PX/1280*960PX) CMOS sensor
<b>Camera</b>	
CPU	high-performance ISP
Image Sensor	1/ 2.9" CMOS
Resolution	1280(H)* 720(V)
Lens	M12 port/3.6,4,6MM
Day/Night	Auto(ICR)
Auto Iris	Auto Iris (DC)
Min. Illumination	Color: 0. 1Lux/F1.2, B/W: 0.001Lux/F1.2 , 0Lux(IR on)
White Balance	Auto/Manual
Exposure mode	Manual / Auto /AP / SP(1~1/10000)
Video Standard	HDCVI port,720P HD output
Control way	video /Audio /RS485 via coaxial cable
<b>AUDIO/VIDEO COMPRESSION</b>	
Frame Rate	PAL: 1280*720@25fps/ NTSC: 1280*720@30fps
Image flip	Support mirror
<b>Function</b>	
Image Settings	Brightness, Contrast, Saturation, Sharpness, etc can be adjusted
S/N	>52dB
3D-DNR	Yes
Privacy Masking	Up to 8 areas
Motion Detection	Yes
Video output	1CH BNC
Menu	NO
Communication Port	support PELCO-D/P, Dahua protocol
<b>Others</b>	
Power supply	DC12V±10%
Power consumption	9W MAX(ICR on, 10.5W MAX)
Working Environment	-30°C~+60°C, 10%~95%
Dimensions(W?D?H)	154.5mm*97.2mm*89.9mm
Weight	750g
Installation	Wall / Ceiling Mount
Certificate	CE , ISO9001