

Key Feature

- HD – SDI 1080P
- Waterproof Camera
- 36 IR LED
- 4mm Lens
- Double shutter WDR
- 8x Digital Zoom
- 130m RG – 59 Cable support



SPECIFICATION

Model	Model PS –302HD
Image Sensor	Panasonic MN34041 12 Bit 60 fps 1080P Sensor
Video Quality	1080P High color reproduction and high sensitivity
Dynamic Range	Double shutter Wide Dynamic Range compensation
Effective Pixels	1944 (H) x 1092 (V)
SDI Video Output	1080P 25/30fps , 720P 50/60fps
CVBS Video Output	PAL and NTSC selected by menu
Electronic Shutter	1/ 50 (1/60) – 1/100,000
Day/Night Mode	Day (Color) / Night (BW) mode , (ICR module Option)
Min.Illumination	0.1 lux/ F1.2 (Color) , 0.01 lux / F1.2 (B/W)
Lens Type	4mm 3M pixel lens / 2.8 – 12mm 2M pixel lens (optional)
Digital Noise Reducer	2D / 3D DNR
Digital Zoom	8X zoom
Flicker	Color Rolling Suppression
OSD	Controlled by RS – 485 from DVR or Button
Communication	RS 485
Protocol	Pelco – P/D , 1200, 2400, 4800, 9600bps
Power	DC12V (AC24V Dual power option)
Driver Capability	RG – 59 cable up to 130 m
Body Construction	Aluminum
Protection	Outdoor/ Indoor use
Operating Temperature	-4 °F ~ 113°F / -20°C ~ 45°C
Dimensions	10.25" x 3.25" x 6.3" / 260mm x 83mm x 160mm
Weight	1.90 lbs / 865g