

4-in-1 MOTION DETECTION AUTO LIGHT 1080P CAMERA



STARVIS Exmor R AUTO LIGHT

Outstanding Visibility under the Starlight

SPECIFICATION



ภาพในสภาวะกลางคืน



ภาพเมื่อตรวจพบการเคลื่อนไหว

Model	PS-325MSL-AFHD
Image Device / DSP	1/2.8" 2.0MP progressive scan IMX291 CMOS + NVP2441H with UTC Function
Scanning Frequency	NTSC: 15,734KHz(H), 60Hz(V); PAL : 15,625KHz(H), 50Hz(V)
Scanning System	2:1 interlace
Number of Effect. Pixels	1945(H) x 1097(V) approx. 2.13M pixels
Image System	PAL / NTSC
Synchronizing System	Internal Sync.
Sensitivity	0.001 Lux@F1.2,AGC ON, 0 Lux at IR ON
Electronic Shutter	Auto /Manual, 1/25~1/100000
Night vision	2pcs array LEDs, IR distance reach 20 meters + 2 White Light LED reach 20m
White-balance	ATW/AWC-SET/INDOOR/OUTDOOR/MANUAL/AWB
AGC	0-15Levels
Noise Reduction	3D-DNR
D-WDR	ON/OFF
Sense-up	ON/OFF
Motion Detection	4 Areas
Back Light Compensation	BLC/HSBLC/OFF
Signal to Noise	More than 52dB
Lens	3.6 mm
Power Consumption	100mA / Max 340mA (LED ON)
Working Environment	Temperature: -40°C to 50°C , Humidity: 95% (No condensation)
Video Output	AHD/TVI/CVI/ Video 1080P / CVBS 960H
Construction	Aluminum with sunshield weatherproof
Dimensions	70(Ø) x 185(L) mm
Weight	350 grams