



Features

- 4/8 CH AHD video input, BNC 8 CH 1080N/ 720P real time recording ,RJ45 ONVIF IPC Max 8CH 1080P (6 Hybrid Mode)
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Multi-mode recording: Manual, Schedule(Regular(Continuous), MD)
- Playback : 1080N 4 CH simultaneously
- Search: Time/Date, MD & Exact search (accurate to second)
- Backup: USB, IE, CMS; support multi-file, file cutting when backup
- Pentaplex: preview, record, playback, backup and remote access
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Multi-user online simultaneously
- HDMI 1080P / 720P output, true high resolution display
- Powerful smart phone surveillance supporting Android, iPhone
- Support 3G Aircard, support QR code scanning by mobile phone
- P2P/Cloud,DHCP, DDNS, PPPoE network protocol and CMS supported

Hybrid Mode:

MODE	Channel Type (Analog + IP)	Playback
	Channel * Resolution / frame	Channel * Resolution / frame
1	8 * 1080N/15 + 0	4 * 1080N/15
2	4 * 1080N/25 + 4 * 1080P/25	2 * 1080P/25
3	2 * 1080N/25 + 6 * 1080P/25	2 * 1080P/25
4	0 + 8 * 1080P/25	2 * 1080P/25

Model	PS-6548AHD2	
Video / Audio input	Video compression	H.264 High Profile Compression
	BNC Video inout	8-CH 1080N / 720P , 8CH 960H CVBSAHD
	Video input interface	8 BNC connector (1.0 Vp-p, 75 Ω) , 1 RJ45
	IP video input	8-CH 1080p IPC (4-CH 1080p Playback)
	Composited video input	4-CH 720P AHD + 4-CH 1080P IPC (4-CH 720P Playback)
	Audio compression	G.711A
	Audio input	4-ch, RCA
	Voice talk input	1-ch, RCA CH1
Video / Audio output	Record/Playback resolution	1080N(960x1080)/720P(1280x720/1280x600)/960H(960x576/960x480)/D1/4CIF(704x576/704x480)/CIF(352x288/352x240)/QCIF(176x144/176x120)
	HDMI& VGA output	1-ch, Resolution:1920x1080p/60HZ,1920x1080p/50HZ,1600x1200p/60HZ,1280x1024p/60HZ,1280x720p/60HZ,1024x768p/60HZ
	Audio output	1*RCA(200-3000mV,5KΩ)
	Main Stream	1080N/720P/960H/D1/HD1/CIF/QCIF
	Extra Stream	D1/CIF/QCIF(1~25/30fps)
	Synchronous playback	1-ch 720P@fps + 3-ch 720P@1fps
HDD	SATA	2 SATA Interfaces for 1 HDD
	Capacity	Up to 4TB capacity for each disk
External interface	Network interface	1 RJ-45 10/100/1000 Mbps Self- Adaptive Ethernet Interface
	Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
	Serial interface	1 RS485 Interface
	USB interface	3*USB 2.0 (Front 1 USB interface)
	Alarm in/out	4/1 optional
General	Power supply	DC 12V/3A
	Consumption	<15W (without HDD)
	Working temperature	0°C-+55°C
	Working humidity	10%—90% RH
	Dimensions(W*D*H)	325*245*50mm
	Weight	1.2KG(without HDD)