

Features:

- Support 8ch 4M-N non real-time encoding;
- Support AHD, TVI, CVI, CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- Mini 1U Case, 1 SATA (Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS, Tawai Platform;
- Support coaxial control

Model:

PS-6608AFHDii

Interface:



Parameters:

	Model	PS-6608AFHD2
System	processor	Hi3520D V300
Video	Codec	H.264+ (Quasi H.265) /H.264
	Encode	8*4M-N@8fps; 8*1080N@12fps(5 in 1)
	Decode	8*4M-N@8fps; 8*1080N@12fps(5 in 1)
	Multi-mode	Analog: 8*4M-N@8fps; 4*1080P@15fps Hybird: 2*1080P(analog)+2*1080P(ip); 4*1080N(analog)+4*960P(ip); IP: 16*1080P; 9*1080P;16*960P;4*5M
	Playback	8ch
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	8*BNC(Support Coaxitron)
	HDMI output	1*HDMI (MAX:1080P)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	4/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
General	HDD	1*SATA interface (Up to 8TB)
	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W(Without HDD)
	Weight	Around 1KG
	Dimension	255(L)* 236mm(W)* 44mm(H)