



### Features

- Support 16 CH 4K -N unreal - time encoding
- Support XVI, AHD, TVI, CVI, CVBS, IP Video Input;
- Support VGA maximum 1080P output, HDMI up to 4K output
- 1.5U Case, 2 SATA (Up to 8TB);
- 1 x 10/100Mbps auto-sending Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the ONVIF protocol;
- Support GB28181 (Optional);
- Cloud service, P2P, Alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, Email, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (IOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari)
- Support for more than twenty language;
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support Coaxial control

Model : PS-6616AUHD

### Interface



Model		PS-6616AUHD	
System	Processor	Hi3531D	
Video	Codec	H.265+/H.265/H.264	
	Encode	16x4K-N@7fps(6in1); 16x5M@6fps(6in1); 16x4M@8fps(6in1); 16x3M@10fps(6in1); 16x1080P@12fps(6in1)	
	Decode	4x4K-N@7fps(6in1); 4x5M@6fps(6in1); 16x4M@8fps(6in1); 16x3M@10fps(6in1); 16x1080P@12fps(6in1)	
	Preview	16x4K-N@16fps(6in1); 16x5M@12fps(6in1); 16x4M@15fps(6in1); 16x3M@18fps(6in1); 16x1080P(6in1)	
	Multi - Mode	Analog	16x5M ; 16x1080P
		Digital to analog	support except 16+16 hybrid mode)
Hybird		16*4M(analog)+16*4M (network) 8*4M(analog)+8*4M (network)	
Playback		16CH	
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record	Manual > Alarm > Motion Detection > Timing	
	Storage Mode	HDD Storage, Network Storage	
	Backup	Network, USB, SATA	
Interface	Video Input	16xBNC (Support Coaxial)	
	HDMI Output	1xHDMI (MAX:4K)	
	VGA Output	1xVGA (MAX:1080P)	
	Audio I/O	6/1	
	Alarm I/O	4/1	
	Ethernet Port	1x10/100Mbps Ethernet port, RJ45 port	
	PTZ Control	1xRS485, Support for multiple PTZ Protocol	
	USB Port	2xUSB2.0 ports	
HDD	2xSATA Interface (Up to 8TB each)		
General	Temperature	0°C - +55°C	
	Humidity	10% - 90% RH	
	Power Supply	12V/4A	
	Consumption	<10W (Without HDD)	
	Weight	Around 1.8 Kg	
	Dimension	310mm (L) x 298mm(W) x 60mm (H)	