



Features :

- Support 32ch 1080N unreal-time encoding;
- HDMI/VGA simultaneous video output;
- BIG 1U Case, 2 SATA(Up to 12TB);
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, TaWai Platform;

Model :

PS-6632AHD2

Interface :



Parameters :

	Model	PS-6632AHD2
System	processor	Hi3531A
Video	Codec	H.264
	Encode	32* 1080N@15fps; 24*1080N; 16* 1080N
	Decode	8* 1080N@15fps; 8*1080N; 16* 1080N
	Multi-mode	Analog:32* 1080N@15fps; 24*1080N; 16* 1080N
		Hybird:8*1080N(analog)+8*960P(network) IP: 32*1080P/16*3M/8*5M
Playback	16ch	
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	32*BNC (Support Coaxitron)
	HDMI output	1*HDMI (MAX:1080P)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	16/1
	Alarm I/O	16/4
	Ethernet port	1*10/100/1000Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
General	HDD	2*SATA interface (Up to 12TB)
	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/4A
	Consumption	<10W (Without HDD)
	Weight	Around 3KG
Dimension	440mm(L)* 290mm(W)* 50mm(H)	