



Parameters:

	Model	PS-6632AQHD	
System	processor	Hi3531A	
Video	Codec	H.264+/H.264	
	preview	32*4M@15fps(AHD); 32*3M@18fps(AHD); 32*1080P (5 in 1)	
	Encode	32*4M@8fps(AHD); 32*3M@10fps(AHD); 32*1080P @15fps (5 in 1) ; 32*720P(5 in 1)	
	Decode	16*4M@8fps(AHD); 16*3M@10fps(AHD); 16*1080P @15fps (5 in 1) ; 16*720P(5 in 1)	
	Multi-mode		Analog:32*4M@8fps(AHD); 32*3M@10fps(AHD); 32*1080P @15fps (5 in 1) ; 32*720P(5 in 1)
			Hybird:16*4M(analog)+16*4M(network)
		IP: 32*1080P;16*3M ;8*5M	
	Playback	16ch	
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record mode	Manual>Alarm>Motion detection>Timing	
	Inquire mode	Inquire by Time/Calendar/Event/Channel	
	Storage mode	HDD Storage, Network Storage	
	Backup	Network, USB, SATA	
Interface	Video input	32*BNC (Support Coaxitron)	
	HDMI output	1*HDMI (MAX:4K)	
	VGA output	1*VGA (MAX:1080P)	
	Audio I/O	16/1	
	Alarm I/O	8/1	
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
	PTZ control	1*RS485, 1*RS232; Support for multiple PTZ protocol	
	USB Port	2*USB2.0 ports	
	HDD	2*SATA interface (Up to 8TB)	
General	Temperature	0 °C - + 55 °C	
	Humidity	10% -90% RH	
	Power supply	12V/4A	
	Consumption	<10W (Without HDD)	
	Weight	Around 3KG	
	Dimension	440mm(L)*290mm(W)* 50mm(H)	

Features:

- Support 32ch 4M unreal-time encoding;
- Support AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output
- BIG1U Case, 2 SATA(Up to 8TB);
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, Tawai Platform;
- Support coaxial control
- Support coaxial upgrade

Model:

6632AQHD

Interface:

