

PS-C5510AQHD

4 in 1 AHD 5.0MP Bullet Camera



Features:

- 5.0MP 1/2.5" low illumination CMOS sensor;
- HD 5MP Resolution, Image clear, Delicate;
- HD lens: 2.8mm, 3.6mm, 6mm optional;
- Day/Night (Auto ICR);
- Auto electronic shutter time;
- IR range: 18 SMD lights 20m-30m;
- Ingress Protection: IP66;
- 500 m transmission without delay;
- Standard coaxial control
- Support coaxial upgrade
- Support four-in-one multi-mode signal output

Parameters

	Model	PS-C5510AQHD
Camera	Sensor	5.0 MegaPixels 1/2.5" low illumination CMOS sensor
	Signal	AHD/TVI@5MP AHD/TVI/CVI@4MP CVBS
	Min. illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W: 0.001 Lux @ (F1.2,AGC ON), 0 Lux with IR
	Shutter time	1/50(1/60)s to 1/10,000s
	Lens	HD lens 3.6mm @F1.8 (2.8mm, 6mm optional)
	Lens mount	M12
	Day&night	IR cut filter with auto switch
	Max.image resolution	2560*2048
	Interface	Video output
Audio I/O		N/A
General	temperature	-10°C- + 60°C
	humidity	10%-90% RH
	Power supply	DC12V±10%
	IR range	18 SMD lights "IR2" :20-30 meters
	Consumption	MAX 3W
	Material	PC plastic+metal
	Ingress Protection	IP66
	Weight	Around 300g
	Dimension	178.9mm*66.9mm*63.5mm

Scenarios:

Apply to roads, warehouses, underground parking and other place which required definition picture quality.

Dimension:

