

OVERVIEW

กล้องสีอินฟราเรดAHDภาพคมชัดสูงถ่ายทอดผ่านสายสัญญาณCoaxialระยะทางถึง300เมตร กล้องมาพร้อมกับอินฟราเรดแบบ 6ARRAY IR LED สำหรับติดตั้งในบริเวณนอกรอาคารโดยเฉพาะตัวกล้องทำจากอลูมิเนียมพร้อมที่บังแดดหน้ากล้อง สำหรับงานมอนิเตอร์ตลอด 24 ชั่วโมง (DAY/NIGHT) ตัวกล้องมีระบบระบายความร้อนพัดลมทำงานอัตโนมัติตามอุณหภูมิ



SPECIFICATION

Image Device/DSP	1080P: 1/ 2.7" Aptina
Resolution	2.1M pixels
Number of Effect. Pixels	1928(H) x 1088(V)
Image System	PAL/NTSC
Electronic Shutter	Auto: 1/50 (60) ~ 1/100,000sec
White-balance	Auto
Synchronizing System	Internal Sync.
Sensitivity	0.01 Lux/F1.2, 0 Lux at IR On
Back Light Compensation	Auto
AGC	Yes
S/N Ratio	More than 52 dB
OSD Button	Yes
Day & Night	ICR IR Cut Auto Switch
D-WDR	On/Off
OSD via UTC	DWDR , DAY/NIGHT COLOR , 960H/1080P Switch
Slow Shutter	Yes
Blower	On/Off Auto
Foggy (Defog)	Auto
Video Output	AHD & CVBS 1.0Vp-p, 75Ω
Lens	6 mm
IR	6ARRAY 25m LED Under 10 Lux by CDS auto control
Blower	Automatically by Thermostat
Power Supply	DC12V 7.5W
Operating Temperature	-10 ~ 50°C
Dimension	110(W) x 100(H) X 330(L) mm
Protection criteria	IP66