TOMURA™

BACK BORAD:

SPECIFICATION:

FEATURES:

◆Adopt 7 inches 800*480 LCD

◆Adopt 3D control rocker

◆Support H.265/H.264 decoding

◆Support PTZ, preset/cruise/pattern operation

◆Support configuration and calling of preset/cruise/pattern

◆Support preview image on the keyboard directly

◆Support remote video keyboard local playback or playback to TV wall

◆Support shortcut operations to the wall

◆Administrators and operators and other multi-level user permission control

◆Support U disk upgrading, network upgrading

◆Support automatic search device within the same network segment

◆Support domain method to add network device

◆Support import and export of keyboard configuration parameter

◆Support the remote configuration and maintenance for the device that have been added

◆Support audio output

Model	PS-KT401
System	
Main processor	High performance embedded processor
Operating system	Embedded Linux
Audio	
Audio input	/
Audio output	1CH
Audio compression standard	G.711a
Video	
Decoding method	H.265/H.264
Decoding resolution	Support 4K/5MP/3MP/1080P/960P/720P local preview remote image, four images display
Interface	
RS232 interface	Support
RS485 interface	Support
Network interface	1 RJ45 100M Adaptive Ethernet
HDMI interface	Support
USB interface	2 USB 2.0(support mouse control）

Auxiliary device	
Remote control rocker	Support 3D rocker control
Display screen	Adopt 7 inch 800*480 LCD display screen
Other	
Operating temperature/humidity	-10°C ~ 55°C/10 % -90 %
Power supply	DC12V（Power plug specification optional）
Device power	≤6W
Device dimension	280*170*40mm
device weight	1.1KG