

Access control

Metal waterproof access control system

Product features

- ◆Working voltage: DC9V-28V
- ◆Waterproof degree: IP68
- ◆With Anti-theft alarm output for external alarm device.
- ◆With built-in anti-theft equipments.
- ◆Support enrolling cards continuously
- ◆Perfect design, with backlight and fashionsilver finish.
- ◆Waterproof design for outdoor use.
- ◆ strong standalone function device, can be used as WG28 reader alone.
- ◆Capacity:2000 user's cards,2000 codes;
- ◆Access ways : cards ,code,card +code.
- ◆Low power :static current less than 30mA.
- ◆Support only keypadd.
- ◆users can reset private passwords.
- ◆Search fast less than 0.1s .
- ◆Wiegand output W26 for card and W34 for codes.
- ◆use keypad to delete lost cards for safety.
- ◆Short-circuit protect :when relay or alarm output shortcircuit, it will shut up output in 100 μ s.

Technical parameters

- Environment Temperature: -45 $^{\circ}$ C~60 $^{\circ}$ C
- Environment Humidity: 10%~90%
- Electric lock output: \leq 3A
- Alarm output: \leq 20A
- Output short-circuit protection time: \leq 100 μ s
- Open-door time: 0~99seconds (adjustable)
- Size: 120*58*18mm

Products types

Model no	Card style	frequency	Reading range
EM Access	EM	125KHz	5-15cm
MF Access	MIFARE	13.56MHz	3-10cm
EM+W Access	EM	125KHz	5-15cm
MF+W Access	MIFARE	13.56MHz	3-10cm

CE FC 
ISO9001:2000

