



### Specifications/Features:

- IR Distance 30M
- Adopting 42PCs  $\phi$ 5mm IR Leds
- Standard lens: 4mm lens
- Dual glass, no IR diffusion and fog
- IP66, outdoor installation

## PS-192AHD

Model	SN-IR13/65BEDN ( Fixed lense )
Image Sensor	1/3"CMOS 1.3 Megapixel
Effective Pixels	1280(H) $\times$ 960(V)
Video Frame Rate	PAL: 25fps/960P NTSC: 30fps/960P
Electronic Shutter	Auto: PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec
Synchronization	Internal
Mini. Illumination	0.001Lux/F1.2(AGC ON), 0Lux IR on
Video Output	1-channel BNC HDVI high definition video output
Max. IR LEDs Length	30m, Smart IR
IR LEDs	f5X42PCS
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D
Lens	4MM
<b>General</b>	
Transmission Distance	Over 500m via 75-3 coaxial cable
Power Supply	DC12V $\pm$ 10%
Ingress Protection	IP66
Power Consumption	Max 4W
Working Environment	-30°C~+60°C / Less than 95%RH
Dimensions(W $\times$ D $\times$ H)	130x70x85mm
Packing	240x160x125mm
Weight	1kg