

## Features:

- >Easy to setup IP cameras
- >Advanced H.264 video compression technology
- >Allow user configure Wi-Fi network, video setting, alarm setting, and micro SD card through Smartphone directly, no need PC to configure anymore!
- >Supports remote PC recording and local recording to Micro SD (up to **64GB** micro SD card externally)
- >P2P (point-to-point) for easy remote access without networking knowledge need
- >Wireless Wi-Fi network connection
- >Motion detection recording, manual recording or schedule recording
- >Alarming record can be stored by email, FTP server.
- >Support mobile Smartphone view remotely (iPhone/Android's smartphone).
- >Supports up to 10 login users at the same time



## Specifications:

<b>Video</b>	Image Sensor	CMOS 1.0 megapixel HD
	Video compression	H.264 high profile, JPEG/BMP snapshot
	Signal system	NTSC/Pal selectable
	Lens	3.7mm
	Min. Illumination	0.1 Lux (IR OFF), 0 LUX (IR ON)
	Frame rate	30fps NTSC, 25fps Pal
	Resolution	1280*720P
	Video adjustment	Brightness, contrast, & saturation
	Video bit rate	32 Kbps ~ 2.5 Mbps
	Zoom	Digital zoom
<b>Audio</b>	Audio compression	G711
	Microphone	Built-in (for audio monitoring and 2-way audio communication). Effective up to 5m (16ft)
<b>Recording &amp; Playback</b>	Recording mode	Motion detection, manual, and schedule
	Storage	Record to local SD (up to <b>64GB</b> , not included); record to remote PC; video or snapshot
	Backup	Remote back up to PC
	Playback	Playback via SD reader; real time remote playback; remotely download and playback
<b>Alarm</b>	Motion detection	VMD (video motion detection)
	Alarm reactions	Alarm photo email; record photo to FTP; record video/photo to SD
	Wireless network	Wi-Fi 802.11 b/g/n
	IP mode	Dynamic IP address; static IP address
	Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNT, & RTSP.

# PS-6206WC

	Online users	10 users at the same time
	Mobile surveillance	iPhone, Android
	Internet viewing	Supports browsers: IE, Firefox, Chrome and Safari
	Remote access	Yes
<b>Software</b>	CMS software	Central management software for recording, remote monitoring, remote access and control, search and playback, and up to 64 multiple cameras surveillance
	User levels for CMS	Administrator, Normal, & Guest (viewing only)
	Camera naming	Supports camera labeling for distinguishing cameras
	Password protection	Yes
<b>CPU &amp; System</b>	Operating system	Embedded Linux OS
	Micro processor	32Bit RISC embedded processor
	System requirement	Microsoft Win98 SE, ME, 2000, XP, Vista, or Windows 7
<b>Others</b>	Indoor/outdoor usage	Indoor
	Operating temperature	-10 ~ 50 °C (+14 ~ 122 °F)
	Humidity	95% RH
	Power	12V 1.5A



Unit weight: 1.35kg