


## 1/3" 1.2M 720P@25fps Vari focal len Blower Housing

### Dimension

### Key Features



- AHD & CVBS BNC interface, Support Over 500m via 75Ω coaxial cable
- long distance real-time transmission
- UTC command OSD menu through Coaxial cable from DVR
- High definition video
- Support Day/Night (ICR)
- 3D-DNR and superior performance of low illumination
- 80M (4 Array IR LED)
- Blower



### SPECIFICATION

Parameter	Model	PS-Z32AHDII
		1 /3" AR0130 sensor
<b>Camera</b>		
CPU		high-performance ISP
DSP		NVP2431H
Resolution		1280(H)* 960(V)
Lens		2.8-12mm
Day/Night		Auto(ICR)
Auto Iris		Auto Iris (DC)
Min. Illumination		Color: 0. 1Lux/F1.2, B/W: 0.01Lux/F1.2 , 0Lux (IR on)
S/N ration		>50dB
White Balance		Auto/Manual
Exposure mode		Manual / Auto /AP / SP(1/50~1/10000)
Video Standard		AHD / CVBS 800TVL
Control way		video via coaxial cable
<b>AUDIO/VIDEO COMPRESSION</b>		
Frame Rate		PAL: 1280*720@25fps/ NTSC: 1280*720@30fps
Image flip		Support mirror
<b>Function</b>		
Image Settings		Brightness, Contrast, Saturation, Sharpness, etc can be adjusted via OSD
3D-DNR		ON/OFF via OSD
Motion Detection		Yes via OSD
Video output		1CH BNC
Menu		YES
Communication Port		UTC
<b>Others</b>		
IR		4 Array LEDs , 80m Range
Power supply		DC12V
Power consumption		7W MAX(ICR on, 8.5W MAX)
Working Environment		-10°C~+55°C, 10%~90%
Dimensions(W/D/H)		175×152×400 mm
Weight		1100g
Protection		IP66
Item		AR0130CS
Drive mode(All-pixel scan)		1412(H) × 1028(V)Approx. 1.45M pixels