



Features

- Support 4ch 1080P real-time encoding;
- HDMI/VGA simultaneous video output;
- Mini 1U Case, 1 SATA(Up to 6TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;

	Model	PS-6604AFHD	
System	processor	Hi3521A	
Video	Codec	H.264	
	Encode	4*1080P@15fps	
	Decode	4*1080P@15fps	
	Multi-mode		Analog:4*1080P@15fps
			Hybird:2*1080P(analog)+2*1080P(network) 4*1080N(analog)+4*960P(network)
	Playback	4ch	
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record mode	Manual>Alarm>Motion detection>Timing	
	Inquire mode	Inquire by Time/Calendar/Event/Channel	
	Storage mode	HDD Storage, Network Storage	
	Backup	Network, USB, SATA	
Interface	Video input	4*BNC (Support Coaxitron)	
	HDMI output	1*HDMI (MAX:1080P)	
	VGA output	1*VGA (MAX:1080P)	
	Audio I/O	4/1	
	Alarm I/O	0/0	
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
	PTZ control	1*RS485, Support for multiple PTZ protocol	
	USB Port	2*USB2.0 ports	
	HDD	1*SATA interface (Up to 6TB)	
General	Temperature	0 °C - + 55 °C	
	Humidity	10% -90% RH	
	Power supply	12V/2A	
	Consumption	<10W (Without HDD)	
	Weight	Around1KG	
	Dimension	255mm(L)* 236mm(W)* 44mm(H)	