



PS-6304CVI/6308CVI

HD-CVI Actual effect



Features:

- Support 4/8ch 1.0Mp and 2.0Mp HD-CVI camera;
- Support 4/8ch 720p real time encoding, Max 8ch synchronous real time playback;
- Support 4/8ch 1080P real time encoding, Max 2ch synchronous real time playback
- Support additional 4ch ONVIF IP camera 720P real time encoding, Max 8ch synchronous real time playback
- Support coaxial dual-way transmission, and the receiver can control the collector via PTZ and zoom control;
- Support long-distance transmission, and 720P can transmit 500m with HD video signal;
- Support tag playback. Tag the important recording point, and realize the specific recording;
- Support quota storage. The HDD can according each channel's require, then allot the storage to each channel and very flexible for each channel's recording;
- Support 2*SATA, each can up to be 3TB.
- Support Cloud Server
- Support 28 languages menu both main monitor and remote clients.

Specifications

HD-CVI compare with Analog

	Model	PS-6304CVI	PS-6308CVI
System	Main Processor	Embedded processor	
	Operating System	Embedded LINUX	
	Log	System/Operation/Data/Event/Video/User	
Video	Video Compression	H.264	
	Input Format	BNC 75Ω :HD-CVI / RJ45: IPC (ONVIF2.0)	
	Input Resolution	HD 720P / 1080P	
	Video Rate	PAL:1~25fps/s; NTSC:1~30fps/s	
	Video Bit Rate	1536Kbps-4096Kbps, User-defined, Max 4096Kbps	
	Stream Type	Video streaming/ Combined streaming	
	Dual-Stream	Support	
Audio	Audio Compression	G.711A/G.711U/PCM	
	Audio Rate	8KHZ, 16Bit	
	Audio Bit Rate	64Kbps	
Video Port	Video Input	4ch *BNC Input	8ch *BNC Input
	Video Output	1ch*VGA, 1ch*HDMI, 1ch*BNC (1.0VPP, 75Ω), HDMI/ VGA/TV Synchronous Output	
	Loop out	NO	
	Matrix output	NO	
Audio Port	Audio Input	1/8ch	
	Audio Output	1ch*BNC Output	
Playback	Recording Mode	Schedule, Manual, Motion, Alarm	
	Recording Playback	Max. 4ch	Max. 8ch
	Backup Mode	HDD, CD Burner, USB Hard Disk, Network Backup	
	Zoom	Mouse Drag Region	
Network	Streaming	Main:1080P/720P/D1 Sub:D1/CIF/QCIF	
Alarm	Alarm Input	4ch	
	Alarm Output	1ch	
HDD	Internal HDD	2*SATA Port	
	Each Storage	3TB	
Port	Internet	1*RJ-45 port, 100M Ethernet Port	
	RS485	1 port	
	USB Interface	3 ports, USB2.0	
General	Power Supply	DC12V/4A	
	Power Consumption	15W (Without HDD)	
	Working Temperature	-10°~+55°C	
	Working Humidity	10%~90%	
	Dimension(W*D*H)	W*D*H: 324x243x52mm	
	Weight	2.5KG (Without HDD)	
	Installation	Desktop / Rack Installation	

