



PS-6516AHD

Features

- 16 CH AHD video input, 16 CH 720P not real time recording
 - RJ45 ONVIF IPC Max 16CH 1080P (5 Hybrid Mode)
 - Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
 - Multi-mode recording: manual / timer / motion
 - Playback : 4 CH simultaneously playback
 - Search: time / calendar, events (alarm / motion)
 - Backup: USB, IE, CMS; support multi-file, file cutting when backup
 - Pentaplex: preview, record, playback, backup and remote access
 - Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
 - Multi-user online simultaneously
 - HDMI 1080P / 720P output, true high resolution display
 - Powerful smart phone surveillance supporting Android, iPhone
 - Support NAT function, support QR code scanning by mobile phone
 - Cloud/P2P, DHCP, DDNS, PPPoE network protocol and CMS supported
- Hybrid Mode:**

16 CH AHD 720p , 2 CH Playback

16 CH AHD 720p , 16 CH Playback

8 CH 960H , 8CH Playback

8 CH 720p & 4 CH IPC 1080p , 2CH Playback

8 CH 960H & 8 CH IPC 1080p , 2CH Playback

8 CH IPC 1080p , 4CH Playback

16 CH IPC 960p , 4CH Playback

Model	PS-6516AHD	
Video / Audio input	Video compression	H.264 High Profile Compression
	BNC Video input	16-CH 720P @18fps AHD , 8CH 960H CVBS + 8CH 720P AHD
	Video input interface	BNC connector (1.0 Vp-p, 75 Ω); PAL / NTSC self-adaptive
	IP video input	16-CH 1080p IPC (4-CH 1080p Playback)
	Composited video input	8-CH 720p AHD + 4-CH 1080p IP (2-CH 1080p Playback)
	Audio compression	G.711A
	Audio input	8-ch, RCA
	Voice talk input	1-ch, RCA
Video / Audio output	Playback resolution	720P / 960H / D1 / HD1 / CIF / QCIF
	HDMI output	1-ch, Resolution:1920x1080p/60HZ,1920x1080p/50HZ, 1600x1200p/60HZ,1280x1024p/60HZ,1280x720p/60HZ,1024x768P/60HZ
	VGA Output	1-ch, Resolution:1024x768/60Hz,1280x720/60Hz, 1280x1024/60Hz,1600x1200/60Hz,1920x1080p/60Hz
	Audio output	1*RCA(200-3000mV,5KΩ)
	Playback resolution	720p / 960H / D1 / HD1 / CIF / QCIF
	Synchronous playback	4-CH 720P @18fps
HDD	SATA	2 SATA Interfaces for 2 HDDs
	Capacity	Up to 4TB capacity for each disk
External interface	Network interface	1 RJ-45, 10/100/1000 Mbps Self- Adaptive Ethernet Interface
	Serial interface	1 RS485 Interface
	USB interface	3*USB 2.0 (Front 1 USB interface)
	Alarm in/out	4/1 optional
General	Power supply	DC 12V/4A
	Consumption	<15W (without HDD)
	Working temperature	0°C - +55°C
	Working humidity	10% - 90% RH
	Dimensions(W*D*H)	325*255*50mm
	Weight	1.4KG(without HDD)