



PS-6548AHD

Features

- 4/8 CH AHD video input, BNC 8 CH 720P real time recording ,RJ45 ONVIF IPC Max 8CH 1080P (6 Hybrid Mode)
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate
- Multi-mode recording: manual / timer / motion
- Playback : 4 CH simultaneously playback
- Search: time / calendar, events (alarm / motion)
- Backup: USB, IE, CMS; support multi-file, file cutting when backup
- Pentaplex: preview, record, playback, backup and remote access
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Multi-user online simultaneously
- HDMI 1080P / 720P output, true high resolution display
- Powerful smart phone surveillance supporting Android, iPhone
- Support NAT function, support QR code scanning by mobile phone
- P2P/Cloud,DHCP, DDNS, PPPoE network protocol and CMS supported

Hybrid Mode:

8 CH AHD 720p , 2 CH Playback

8 CH AHD 720p , 4 CH Playback

8 CH 960H , 8CH Playback

4 CH 720 p & 4 CH IPC 1080p , 2CH Playback

4 CH 960H & 8 CH IPC 1080p , 2CH Playback

4 CH 720p & 4 CH IPC 720 p , 4CH Playback

8 CH IPC 1080p , 2CH Playback

Model	PS-6548AHD	
Video / Audio input	Video compression	H.264 High Profile Compression
	BNC Video inout	8-CH 720P AHD , 4CH 960H CVBS + 4CH 720P AHD
	Video input interface	8 BNC connector (1.0 Vp-p, 75 Ω) , 1 RJ45
	IP video input	8-CH 1080p IPC (4-CH 1080p Playback)
	Composited video input	4-CH 720P AHD + 4-CH 1080P IPC (4-CH 720P Playback)
	Audio compression	G.711A
	Audio input	8-ch, RCA
	Voice talk input	1-ch, RCA
Video / Audio output	Playback resolution	720p / 960H / D1 / HD1 / CIF / QCIF
	HDMI output	1-ch, Resolution:1920x1080p/60HZ,1920x1080p/50HZ,1600x1200p/60HZ,1280x1024p/60HZ,1280x720p/60HZ,1024x768p/60HZ
	VGA Output	1-ch, Resolution:1024x768/60Hz,1280x720/60Hz,1280x1024/60Hz,1600x1200/60Hz,1920x1080p/60Hz
	Audio output	1*RCA(200-3000mV,5KΩ)
	Playback resolution	720P / 960H / D1 / HD1 / CIF / QCIF
	Synchronou s playback	1-ch 720P@fps + 3-ch 720P@1fps
	HDD	SATA
Capacity		Up to 4TB capacity for each disk
External interface	Network interface	1 RJ-45 10/100/1000 Mbps Self- Adaptive Ethernet Interface
	Serial interface	1 RS485 Interface
	USB interface	3*USB 2.0 (Front 1 USB interface)
	Alarm in/out	4/1 optional
General	Power supply	DC 12V/3A
	Consumption	<15W (without HDD)
	Working temperature	0°C-+55°C
	Working humidity	10%—90% RH
	Dimensions(W*D*H)	325*255*50mm
	Weight	1.2KG(without HDD)