



- ◆ 1/3" SONY Super HAD CCD
- ◆ DSP: Effio-E
- ◆ Resolution: 700TVL
- ◆ Min. illumination: 0Lux (IR ON)
- ◆ IR distance: 80m(2xArray LED)
- ◆ OSD menu, IP66, cable bracket included, DC12V



SPECIFICATION

Model	PS-402A
Pick-up device	1/3" SONY Super HAD CCD
Effective pixels	NTSC: 976x494,PAL: 976x582
Resolution	Color 700TVL
Min. illumination	0lux(IR on)
Sync system	Internal
Scan system	2:1 interlace
S/N ratio	more than 50dB
Lens	6mm
Electronic shutter	1/50 – 1/100,000
Digital WDR	Off/On(0-63 level adjustable)
BLC	HLC/BLC/OFF
White balance	Auto
Motion detection	Off/On(4 areas)
Privacy zones	Off/On(8 areas)
Mirror function	Off/On(Horizontal mirror)
Image adjustment	Contrast,Sharpness,Saturation
AGC	High/Mid/Low/Off
Gamma	0.45/Custom(0.05-1.0)
Display mode	CRT/LCD/USER
OSD menu	Simplified Chinese/English
Video output	1.0Vp-p Composite Video Output, 75 Ohm
IR distance	60-80m
Power supply	DC12V
Power consumption(Max)	2A (IR on)
Operation temp	-20°C ~ 50°C
Housing	Camera Built-in IP66 Housing and managed cable Bracket.

WDR (Wide Dynamic Range)



HLC



Privacy Masking

