

750TVL 1/3" SONY Super HAD II CCD 960H IR Cylinder Camera



Feature

- ◆ 1/3" SONY Super HAD II CCD 960H
- ◆ DSP : Sony Effio-A
- ◆ Image Resolution: Color 750TVL
- ◆ Min. illumination: 0 Lux(IR ON), Color: 0.03Lux/F1.2, B/W: 0.00009 Lux/F1.2(Sens-up ON)
- ◆ Smart IR, Sens-up, Motion Detection, Privacy mask, BLC
- ◆ HLC, CRR, D-WDR, Digital image stabilization, Electronic shutter adjustable
- ◆ Mirror, Multi WB Models, 3DNR, Digital zoom
- ◆ OSD menu, Cable managed bracket, IP66, IP66, Lighting-proof, DC 12V

Applications

PS-HZ80 700TVL 1/3" SONY Super HAD II CCD 960H IR Camera provide a High resolution security solution where darker and empty-illumination environment required such as highway tolling system, electronic police system, urban business street, warehouse, basement parking, bar, pipeline, etc.

Model	PS-HZ80
Param	
CAMERA	
Sensor	1/3" SONY Super HAD II CCD 960H
Effective pixels	NTSC:976x494,PAL:976x582
Resolution	750TVL
Min.illumination	0 Lux(IR ON)
Scan System	2:1 interlace
Sycn System	Internal
Lens	4-9mm manual
Electronic shutter	Auto(1/60(1/50)~1/100,000) /Fixed/ Manual
S/N Rate	52 dB(AGC OFF)
Video Output	1.0Vp-p composite video output, 75Ω
OSD MENU	
White Balance	AWB/ MANUAL/ ONE PUSH/ FIXED/ CRR/ USER1/ USER2
NR	3D Noise reduction
Image Adjustable	Lightness/ contrast/ Sharpness
DWDR	Normal/ LIGHT/ FULL
BLC	BLC/HLC/OFF
AGC	ON/OFF
Day/Night	B/W, COLOR, AUTO, EXT
Privacy Zones	ON/OFF(15 zones)
Motion Detection	ON/OFF(4 zones)
Mirror	H-Roll over/V--Roll over/ Center-Roll over/ OFF
Gamma	0.45(Default)
OSD Menu	Chinese/ English

GENERAL	
IR Distance	40-50m(2*Array LEDS) Constant current source lamp plate
Protection level	IP66
Power Supply	DC12V± 10%
Power Consumption	560mA±10mA(IR ON)
Operating Conditions	-20°C ~ 55°C/ 0%-90%
Dimensions	121(W)*90(H)*253(L)mm
Weight/PCS	About 800 g
Qty	8
Carton Dimensions	605(L)*390(W)*315(H)

Dimension

