




DIMENSION



FUNCTION



PS-B5545
STANDARD BOX CAMERA

FEATURES

- ▶ Ultra High Resolution (650TVL)
- ▶ Super Sensitivity (0.00002Lux)
- ▶ 2D+3D DNR (Digital Noise Reduction)
- ▶ Digital Slow Shutter (Sense- up)
- ▶ D-WDR (Wide Dynamic Range)
- ▶ RS485 Communication
- ▶ True D&N ICR (Optional)

SPECIFICATION

ITEM		NTSC	PAL
C C D	Total Pixel	811(H) x 508(V)	795(H) x 596(V)
	Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
	Sensor	1/3" SONY SUPER HAD II CCD	
	Scanning System	2:1 Interlace	
E L E C T R I C A L	Resolution	More than 650 TV Lines	
	Video Output	1.0Vp-p Composite Signal (75ohm)	
	S/N (Y signal)	52dB (AGC OFF,Weight ON))	
	Min.Illumination	0.01Lux(Sense-up Auto 0.00002 Lux)	
	White Balance	AUTO/ATW/ MANUAL	
	Electronic shutter speed	1 / 60 sec ~ 1 / 100,000 sec 1 / 50 sec ~ 1 / 100,000 sec	
	3D-DNR (Digital Noise Reduction)	OFF / ON Selectable	
	Sense-Up	Auto/OFF(~x2~ ~x1024)	
	D&N Selection	AUTO / COLOR / BW / EXT	
	WIDE BLC (D-WDR)	OFF / ON Selectable	
	BLC	HLC/BLC/OFF	
	Defect Pixel Compensation	Built-In OSD	
	SMART LED Control	Built-In OSD	
	Motion Detection	ON/OFF	
	Privacy Masking	ON/OFF	
	Gamma	0.45	
Mirror	Built-In OSD		
Sharpness	ON/OFF		
Pan Focus Control	Built-In OSD		
Multi Language	Available		
O.S.D	Available		
Operating temperature/Humidity	-10°C ~ 50°C/0-95% RH		
Power Supply	DC 12V±10%		
Dimensions	38mm(W) x 38(D)/42mm(W) x 42(D)		
Weight	Appx. 100g		

