

# TP-1007DN-IR

## BOX CAMERA



### SPECIFICATION

|                         |  |
|-------------------------|--|
| MODEL                   | TP-1007DN-IR                                     |
| PICK-UP DEVICE          | 1/3" Interline Transfer CCD                      |
| PICTURE ELEMENTS        | NTSC: 510(H) X 492(V)                            |
|                         | PAL: 500(H) X 582(V)                             |
| SYNC SYSTEM             | Internal sync                                    |
| HORIZONTAL RESOLUTION   | 420 TV lines                                     |
| MINIMUM ILLUMINATION    | 0.4 Lux / F1.4                                   |
| LENS MOUNT              | CS mount or C mount with 5mm adaptor ring        |
| AUTO WHITE BALANCE      | Auto   |
| BACK LIGHT COMPENSATION | On/off switchable                                |
| GAMMA CORRECTION        | 0.45   |
| AUDIO                   | Built-in high sensitive microphone               |
| S/N RATIO               | Over 48dB  |
| ELECTRONIC SHUTTER      | 1/60(1/50) to 1/100,000(1/110,000) on/off switch |
| IRIS CONTROL            | Video/Direct Drive Auto Iris Switch              |
| VIDEO OUTPUT            | 1.0 Vp-p , 75ohm                                 |
| POWER SOURCE            | DC 12V $\pm$ 10% or AC 110V/AC220V (optional)    |
| POWER CONSUMPTION       | Approx. 3.0W                                     |
| WORKING TEMPERATURE     | -10 °C to +45 °C                                 |
| Gain Control            | Yes  |
| DIMENSIONS              | 60(W) x 50(H) x 108(D) mm                        |
| WEIGHT                  | Approx. 280g                                     |