

# PS-403F IR DOME Camera

## Key Features

- Ultra High Resolution (700TVL)
- 2D+3D DNR (Digital Noise Reduction)
- Digital Slow Shutter (Sense-up)
- D-WDR (Wide Dynamic Range)
- 4mm CS Lens
- 2 ARRAY IR LED
- 30m IR Range



## SPECIFICATION

ITEM		NTSC	PAL
C	Total Pixel	811(H) x 508(V)	795(H) x 596(V)
	Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
D	Sensor	1/3" SONY Ex-view CCD	
	Scanning System	2:1 Interlace	
E L E C T R I C A L	Resolution	700 TV Lines	
	Video Output	1.0Vp-p Composite Signal ( 75ohm )	
	S/N (Y signal)	50dB	
	Min.Illumination	0Lux/IR ON	
	White Balance	AUTO/ATW/ MANUAL	
	Electronic shutter speed	Adjustable: 1 / 60 sec ~ 1 / 100,000 sec NTSC 1 / 50 sec ~ 1 / 100,000 sec PAL	
	3D-DNR(Digital Noise Reduction)	OFF / ON Selectable	
	SLOW SHUTTER	DIGITAL SLOW SHUTTER	
	FACE DETECTION	FACE NOTE/FACE ZOOM	
	VIDEO ANALYTIC	VIRTUAL FENCE	
	D-WDR	OFF / ON Selectable	
	BLC	HLC/BLC/OFF	
	DEMIST	DEMIST/3D-DNR	
	Motion Detection	ON/OFF	
	Privacy Masking	ON/OFF	
	M I R R O R	Mirror	Built-In OSD
Sharpness		ON/OFF	
Multi Language		Available	
O.S.D		Available	
Power Supply		DC 12V	
Operation temp		-40 C - 50 C	
Dimensions	70mm(Ø)x132mm(H)		