



## PS-HB85A Dome IR CAMERA



- 1/3" SONY Super HAD II WD CCD(960H)
- Effio-A Resolution: 750TVL
- Min. illumination 0Lux(IR on)
- IR leds: 24xΦ5, IR distance: 15m
- Lens 3.6mm Angle of View >90°
- D-WDR,BLC, HLC,3DNR,Sense-up, Smart IR
- Zoom, UTC function, Lighting-proof, DC12V





## **SPECIFICATION**

## **Optional Accessory:**







Model	PS-HB85A
Pick-up device	1/3" SONY Super HAD II 960H CCD
Effective Pixels	NTSC:976x494,PAL:976x582
Sync system	Internal
Resolution	750TVL
Min. Illumination	0.00009LUX/F1.2 , 0Lux (Sens-up on )
S/N	More than 52dB
<b>Electronic Shutter</b>	NTSC:1/60~1/100,000, PAL:1/50~1/100,000
Lens	3.6 mm
Gamma	Auto/Manual
White Balance	Auto
Electronic Iris	Auto
AGC Gain Control	High / Low
BLC	On / Off
Day & Night	EXT
Video Output	1.0Vp-p Composite Video Output,75ohm
IR distance	15m
LED Life	More than 10,000 hours Constant Current Circuit IR
Power Supply	DC12V ±10%
Power Consumption	Constant Current DC8-18V:100mA, IR ON/300mA
Operating Temp. / Humidity	-20°C ~ 55°C , 0%-90%RH
<b>Environment resistant</b>	IP65