

PS-TB29

DOME CAMERA



- ◆ 1/3" SONY Super HAD II CCD
- ◆ DSP: NVP2030
- ◆ Resolution: 480TVL
- ◆ Min. illumination: Color: 0.02Lux/F1.2; B/W: 0.002Lux/F1.2
- ◆ Electronic shutter adjustable, D-WDR, BLC, HLC, Anti-flicker, Mirror, Motion detection, Lens shade control, Privacy zone
- ◆ OSD menu, Lightning proof, 3D bracket adjustable, DC12V



SPECIFICATION

Model	PS-TB29
Pick-up device	1/3" SONY Super HAD II CCD
Effective pixels	NTSC:510*492,PAL:500*582
Resolution	Color 480TVL
Min. illumination	Color: 0.02Lux/F1.2; B/W: 0.002Lux/F1.2
Sync system	Internal
Scan system	2:1 interlace
S/N ratio	more than 50dB
Lens	Auto Iris 4-9mm Korea Lens.
Electronic shutter	Auto/Anti-flicker/Manual
Digital WDR	On
BLC	HLC
White balance	ATW1/ATW2/MANUAL/FIXED
2DNR	OFF/ON
Day&Night	Auto/B/W/Color/EXT
Motion detection	Off/On (4 areas)
Privacy zones	Off/On (8 areas)
Mirror function	Off/On (Horizontal mirror)
Image adjustment	Contrast, Sharpness, Saturation
AGC	High/Mid/Low/Off
Gamma	0.45/Custom (0.05-1.0)
Display mode	CRT/LCD/USER
OSD menu	Simplified Chinese/English
Video output	1.0Vp-p Composite Video Output, 75 Ohm
Power supply	DC12V± 10%
Power consumption(Max)	200mA/DC12V
Operation temp	-20°C ~ 50°C

WDR (Wide Dynamic Range)



HLC



Privacy Masking

