



PS-D9945

VANDALPROOF DOME CAMERA

FEATURES

- ▶ Ultra High Resolution (650TVL)
- ▶ Super Sensitivity (0.00002Lux)
- ▶ 2D+3D DNR (Digital Noise Reduction)
- ▶ Digital Slow Shutter (Sense-up)
- ▶ D-WDR (Wide Dynamic Range)
- ▶ Intelligent IR Control (Smart IR)
- ▶ 2.8-11 Varifocal Auto Iris Lens
- ▶ Weatherproof (IP66)
- ▶ RS485 Communication (Optional)
- ▶ 30 IR LED
- ▶ TRUE D&N ICR (Optional)
- ▶ 12VDC/24VAC Dual Power(Optional)

SPECIFICATION

ITEM		NTSC	PAL
C C D	Total Pixel	811(H) x 508(V)	795(H) x 596(V)
	Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
	Sensor	1/3" SONY SUPER HAD II CCD	
	Scanning System	2:1 Interlace	
E	Resolution	More than 650 TV Lines	
L	Video Output	1.0Vp-p Composite Signal (75ohm)	
E	S/N (Y signal)	52dB (AGC OFF,Weight ON)	
C	Min.Illumination	0.01Lux(Sense-up Auto 0.00002 Lux)	
T	White Balance	AUTO/ATW/ MANUAL	
R	Electronic shutter speed	1 / 60 sec ~ 1 / 100,000 sec 1 / 50 sec ~ 1 / 100,000 sec	
I	3D-DNR (Digital Noise Reduction)	OFF / ON Selectable	
C	Sense-Up	Auto/OFF(~x2~ ~x1024)	
A	D&N Selection	AUTO / COLOR / BW / EXT	
L	WIDE BLC (D-WDR)	OFF / ON Selectable	
	BLC	HLC/BLC/OFF	
	Defect Pixel Compensation	Built-In OSD	
	SMART LED Control	Built-In OSD	
	Motion Detection	ON/OFF	
	Privacy Masking	ON/OFF	
	Mirror	Built-In OSD	
	Sharpness	ON/OFF	
	Pan Focus Control	Built-In OSD	
	Multi Language	Available	
	O.S.D	Available	
	Operating temperature/Humidity	-10°C ~ 50°C/0-80% RH	
	Power Supply	DC 12V	
	Dimensions	115mm(H)x136mm(D)	

