





Key Features

- H.264/MJPEG
- 720P full real-time recording
- Support I8S, plug and play
- Support mobilephone, IE browser monitoring
- POE
- Gimbal cable bracket included
- IP66, Lightning-proof, DC12V

Dimension



WIRE INTERFACE

1. Power Supply
2. Network Interface
3. Analog video output

SPECIFICATION

Model	PS-622HD-PV
CAMERA	
Sensor	1/4" OV 1.3 MP Progressive scan CMOS
Min.illumination	0Lux/F1.4 (IR ON)
Electronic shutter	Auto/Manual (1/25~1/10000)
Day/Night	Auto, B/W, color, EXT
Video parameter	DWDR, mirror, 3D noise reduction, sharpness/ lightness adjustable
IR distance	10-15M (30xΦ5 IR leds)
Lens	2.8mm M12 lens (6mm/8mm M12 lens optional)
Lens interface	M12
AUDIO/VIDEO COMPRESSION	
Video compression	H.264/MJPEG
Encoding features	Dual-stream: main-stream PAL: 1280X720 25fps; NTSC: 1280X720 30fps
Max. image resolution	1280X720
Encoding system	Constant bit rate, variable bit rate optional
Video bit rate	
Stream type	Complex stream/ video stream
Audio compression	/
Audio bit rate	/
NETWORK	
Password protection	Support
Character display	Support (Channel, Date)
Mobile surveillance	Apple, Android

INTERFACE	
Network interface	RJ45 10M/100M adaptive
GENERAL	
Operating conditions	-20°C ~ 55°C/0%-90%
IP grade	IP66
Power supply	DC12V/ POE
Power consumption	<6W
Dimensions	66(W)*66(H)*166.7(L)mm
Weight (net weight)	366g
WIRE INTERFACE	
1. Power supply 2. Network interface	