



- 1/3" Sony CCD sensor
- 0.2 Lux , 0 Lux at IR on / F2.0
- 420 TV lines
- 80 IR LED Distance 30M
- 4~9mm Varifocal Lens
- DC 12V / AC220V

SPECIFICATION

Image Device	1/3" Sony CCD sensor
Scanning Frequency	NTSC:15,734KHz(H), 60Hz(V) PAL: 15,625KHz(H),50Hz(V)
Scanning System	Internal
Effective Pixels	NTSC: 512(H) x 492(V) PAL:512(H) x 582(V)
Electronic Shutter	NTSC:1/60- 1/100,000sec (Auto); PAL:1/50-1/100,000sec (Auto)
Horizontal	420 TV lines
White-balance	Auto white balance (2500°K~9500°k)
Synchronizing System	Internal
Sensitivity	0.2 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB (AGC off)
IR Distance	30 Meters (Based on: object of view reflected IR light)
IR LED	80 pcs
IR View Angle	View angle: 70°, Beam spread: 40°/per LED
IR Wavelength	850nm ± 25nm
LED Life	More than 10,000 hours
Lens	4~9mm Varifocal Lens
Power Supply	DC 12V 1A (not included) /AC 220V
Temperature	Operating: -10 to 50°C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	Aluminum with sunshield weatherproof
Dimensions	285(L) x 138(W) x 120(H) mm
Weight	TBD