

The World's First 600 TV Line



FEATURES

- 1/3"Sony CCD
- WDR/BLC/ECLPS
- Ultra High Resolution 600TVL
- 3D-DNR
- 6X Digital Zoom
- 8 Zone Motion Dection
- Privacy Region Shielded
- O.S.D Menu
- RS485 Remote Control
- High Light Compensation
- Vandalproof Dome
- 3 Axis Structure
- 6MM CS lens
- 72pcs O 5 IR leds 60m IR Distance

OSD Menu



WDR (Wide Dynamic Range)



3D-DNR (Digital Noise Reduction)



HLC



Privacy Masking



SPECIFICATION

Model No.	PS-K3160
Power	DC12±10% Max 2.0W
Sensor	1/3 inch Sony DS CCD
Total Pixels	NTSC: 811(H)×508(V)
	PAL: 795(H)×595(V)
Effective Pixels	NTSC: 768(H)×494(V)
	PAL: 752(H)×582(V)
Scanning System	2:1 Interlace
Sync. System	Internal/Line lock
O.S.D	Available
Dynamic Range	52dB (×128)
Backlight Compensation	WDR/BLC/OFF selectable
Resolution	Color 600TVL
S/N(Y Singal)	52dB (AGC OFF)
Mini Illumination	Color Model: 0.02(0.6) Lux(Sens-up OFF) @50IRE
	B/W Model: 0.0001(0.1) Lux(Sens-up OFF)
White Balance	ATW/AWC/Manual/FIXED 2,500°K-9,000°K/ Outdoor (1,800°K~10,500°K) Indoor (4,500°K~8,500°K)
Electronic Shutter Speed	NTSC:1/60sec-1/120,000sec
	PAL:1/50sec-1/120,000sec
Sens-up	Auto/Fixed/Off(selectable limit ×2~×512)
Gain Control	Low/Middle/High/Off selectable
3D-DNR	Off/On (1~63 level adustable)
Motion Dection	On/Off (8 Zone, Alarm output)
Privacy	On/Off (8 Zone)
Mirror (H-REV)	ON/OFF
FLIP(V-REV)	ON/OFF
Freeze	ON/OFF
SHARPNESS	ON/OFF (Level Adjustable)
D/N Selection	Color/Black&White/Auto/Exit
STABILIZER	ON/OFF
Digital Zoom	On(×6)/Off
Blemish compensation	256 Point (Even 128 point, ODD 128 point)