

Features and benefit

- 1.High-definition color LCD display, the unique open design of the keyboard.
- 2.Have a professional access control function of the time zone hours, access privilege features, and a professional access control interface.
- 3.Supports multi-user recognition by free setting between the two users and five users.
- 4.Supports a variety of identification test mode: Fingerprint, card, password, any combination.
- 5.Through RS485 or TCP/IP multi-networked control.
- 6.Support for ID cards and IC card

- รองรับการระบุบุคคลโดยลายนิ้วมือ ทาบบัตร รหัสผ่าน หรือรวมกัน
- เชื่อมต่อระบบควบคุมการเข้า-ออกทั่วไปด้วย Wiegand 26/34
- เชื่อมต่อเป็นหัวอ่านภายนอกโดยใช้คู่กับ PS-MF950



PS-MF11

Model	PS-MF11
Working voltage	12V
Static working current	150mA
Dynamic current	250mA
Relay contact current	3A 120VAC/28VDC
LCD	2.4" TFT color screen
Operation temperature	0°C~ 45 °c
Dimension (mm)	185 x 80 x 35
Relative operation humidity	20% - 60%
Fingerprint sampler	High-hardness optical fingerprint sampler
Keyboard	20 tact switch
Main board	Smart KM dual-core low-consumption structure
Core algorithm	HSA 8.0
FRR	≤1%
FAR	≤0.0001%
Reaction time	<1S
Working mode	Offline/online
Sensitivity level setting	1: N/1: 1
Identification mode	Fingerprint-password-card, Fingerprint+password, Fingerprint+card, card+password, Card+fingerprint+password

Capacity of fingerprint	2,000
Capacity of management record	1,000
Capacity of in and out records	60,000
Communication mode	RS485, TCP/IP , USB backup
Language display	Thai , English , Simplified/Traditional Chinese
Vocal instruction	Thai/English high quality voice
Name display	Long name display
Time group	30 groups
Time section	50 sections
Alarm	Alarm for removal prevention, alarm for overtime opening, Alarm for tamper resistance, alarm for external in put points
Fire fighting blocking	Available
Threatening alarm	Available
Exit button	Available
Wigand interface	Supports standard 26/34 input and output
Tamper resistance	Available
Real-time monitor	Available
Validity	Available
Proximity card reader	ID/IC card support
Bell ring function	20 groups of rings
Doorbell interface	Available