


TVB001

Twisted Pair VIDEO BALUN

- Eliminate interference under long range cabling caused by "Impedance Matching", add TVB001 BALUN at "connecting point" between two-wire connections for compensation.
- Including 4 pieces UY connectors for connection.



Before use



After use

CHB001H Hi Frequency Interference Blocker



CHB001HT



CHB001HR



Before use



After use



Before use



After use

Features:

- Perfect to eliminate Hi Frequency Interference.
- Video & Audio over one Coax Cable.
- Working distance: 600 meters (RG59), 180 meters (UTP cable).
- S/N Ratio on video signal: 42dB, S/N Ratio on audio signal: 40dB.
- Including transmitter and receiver, two power adapter.

Specifications:

- VIDEO INPUT: 1 Vp-p A75 Ohms (BNC Connector)
- VIDEO OUTPUT: 1 Vp-p A75 Ohms (BNC Connector)
- AUDIO INPUT: 600 Ohm Internal Impedance, 1.0Vp-p
- AUDIO OUTPUT: RCA 1.0Vp-p
- WORKING RANGE: 400 meters for RG59 CABLE, 600meters for RG6U cable
- POWER Supply: 12VDC 500mA
- POWER CONSUMPTION: 150mA CHB001HT, CHB001R
- DIMENSIONS W x H x D mm: 102.5x67x27 CHB001HT
- DIMENSIONS W x H x D mm: 91x67x27 CHB001HR